

AUTOMATIC DIGITAL MULTIMETER WITH AUTOMATIC RANGE SELECTION (600 V)

Article number: 111404

Digital Multimeter Automatic, with automatic range selection (600 V). Professional multimeter with automatic range selection, AC/DC voltage measurement up to 600 V, AC/DC current measurement up to 10 A, resistance measurement up to 40 m Ω , temperature (up to 500°C), capacitance (up to 100 μ F) and frequency measurement (up to 5 mhz), overvoltage category CAT III 600 V, CAT IV 300 V, optical and acoustic continuity test, diode test, large LCD display, with display illumination, data hold function, protection



Attribute	Value
Display	digital
Multiple display	No
With screen backlighting	No
Max. Voltage measuring range AC	600
Max. Voltage measuring range DC	600
Max. Current measuring range AC	10
Lowest resolution alternating current	10 μ A
Max. DC current measuring range	10
Measuring range selection	automatisch
Lowest resolution AC voltage	1 mV
Lowest resolution DC voltage	0,1 mV
Lowest resolution direct current	10 μ A
Max. resistance measuring range	40
Milliohm measurement with 4-wire technology (Kelvin connection)	No
Lowest resolution resistance	0,1 Ohm
Temperature measurement RTD	No
Temperature measurement	Yes
Temperature measurement TC	Yes
Max. Temperature measuring range	500
Lowest resolution temperature	1 °C
Capacitance measurement	Yes

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

Max. capacitance measuring range	200
Lowest resolution capacity	0,001 µF
Frequency measurement	Yes
Max. Frequency measuring range	500
Lowest resolution Frequency	0,001 Hz
Continuity test/diode test	Yes
Nominal test voltage 10 V	No
Nominal test voltage 50 V	No
Nominal test voltage 100 V	No
Nominal test voltage 250 V	No
Nominal test voltage 500 V	No
Nominal test voltage 1000 V	No
Cable length measurement	No
Line symmetry test for two-wire connections a-b-E	No
Power and energy measurement	No
Harmonic analysis/power quality	No
With level measurement (dB)	No
Relative value measurement	Yes
Inductance measurement	No
Conductivity measurement	No
Continuity test	Yes
Instantaneous value memory (data hold)	No
Maximum value memory	No
Minimum value memory	No
Peak value memory	No
True RMS value measurement (TRMS)	No
Duty cycle measurements	No
Speed measurement	No
Interface	No
Measured value memory	No
Bluetooth interface	No
IR interface	No
Circuit breaker	No
Measuring circuit category	CAT III
Max. Voltage Measuring circuit category	600
Power supply	Batterie

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de



Explosion-tested version

No

GTIN: 4021103114049

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de