

CIMLED STRIPE 25

Article number: 111530

CimLED Stripe 25 is a high-intensity LED strip for indoor and outdoor use. The LED strip is 25 m long and compactly rolled up on a cable drum. This makes it easy to transport and store. It is suitable for illuminating various work and traffic zones in building shells (e.g. corridors, stairwells, etc.). With a luminous flux of 1,300 lm/m, the LED strip provides bright illumination and is protected against dust and water jets in accordance with IP65.

Attribute	Value
Protection class (IP)	IP65
Length	2500 mm
Execution	Band
Mounting type	Aufbau/Einbau
Width	15 mm
Diameter	- mm
Light color	weiß
Conductor cross-section	0.75 mm²
Type of wiring	mit Durchgangsverdrahtung
Number of poles	2
Color temperature	4000 K - 4000 K
Light source	LED nicht austauschbar
Max. System performance	200 W
With protective cover	Yes
Connection type	löten
Color rendering index CRI	80-89
Height/depth	7 mm
Protection class	Ш
Self-adhesive	No
Adjustable luminous flux	nein
Number of light sources per meter	240
Number of light sources per foot	73

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de



,	
Lamp wattage per meter	10 W
Lamp wattage per foot	3 W
Luminous flux per meter	1100 lm
Luminaire luminous efficacy	110 lm/W
Voltage type	AC
Lamp voltage	220 V - 220 V
Beam angle	180°
Operating device	nicht erforderlich
Suitable for dimmers	No
Replaceable operating device	No
Energy efficiency class of the light source according to EU Directive 2019/2015	Е
Rated service life L70/B50 at 25 °C	25000 h
Luminous flux maintenance with average service life 50,000 h at 25 °C ambient temperature	80 %
Failure rate with average service life of 50,000 h at 25 °C ambient temperature (tq)	0%
Protection class (NEMA)	3R
Constant luminous flux control	No
Power factor	0.85
Power factor Adjustable color temperature	0.85 nein
Adjustable color temperature	nein
Adjustable color temperature Adjustable beam angle	nein nein
Adjustable color temperature Adjustable beam angle Smallest bending radius	nein nein 3 mm
Adjustable color temperature Adjustable beam angle Smallest bending radius Length of the individual sections	nein nein 3 mm 1000 mm
Adjustable color temperature Adjustable beam angle Smallest bending radius Length of the individual sections With end piece	nein nein 3 mm 1000 mm No
Adjustable color temperature Adjustable beam angle Smallest bending radius Length of the individual sections With end piece With connection set	nein nein 3 mm 1000 mm No
Adjustable color temperature Adjustable beam angle Smallest bending radius Length of the individual sections With end piece With connection set Compatible with Apple HomeKit	nein nein 3 mm 1000 mm No No

GTIN: 4021103102053

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de