KATIMEX® KATI®BLITZ MINI 15 M, TAPE 1.2 MM Ø

Article number: 142060

Attribute

Length

Material

Color

Shape

Head shape

Material quality

Threaded connection

DATA SHEET

Katimex[®]-Kati[®]Blitz Mini. Kati[®]Blitz Mini was specially developed for fiber optics for the growing demands of subsequent fiber optic installations in existing, already occupied empty conduits. Where conventional pull-in devices are no longer sufficient, the Kati[®]Blitz Mini shows its full size with a fiber optic profile of only 1.2 mm Ø. In particular, the Kati[®]Blitz Mini simplifies the subsequent installation of fiber optic cables, or often makes it possible in the first place, making it the ideal

helper for pulling in fiber optic cables in buildings. The specially developed Polykat Mini fiber optic profile is characterized, in addition to its small diameter, by high tape strength and shear stability, as well as a very small bending radius of 15 mm. Together with the Flexi Probe Mini, whose special contour allows it to pass through tight spots and curves, and a low-friction guide hose that guides and protects the belt, the insertion process into an occupied empty pipe is quick and easy. In addition, the quide hose protects against breakage when the tape is pulled back. Included accessories: 5 Flexi probes M 2.5 with internal thread, 7 initial sleeves M 2.5 with external thread, 1 guide hose 2.5 m with locking sleeve, 1 insulating tape 15 mm for fastening the fiber optic cable to the Flexi probe, 1 abrasive pad 50x50 mm, 1 special adhesive 3g. Product advantages at a glance: Flexi-Probe Mini: special contour for passing through tight spots and curves. Rotating belt cassette: by turning



CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.

Value

Kunststoff

sonstige

sonstige

sonstige

rund

Yes

15

SICHER SEIT 1827.



Twisted	No
Diameter of cable guide head	No 2,5 Insta
Field of application	Insta
Width/diameter of the pull-in wire	1,2 Gehä
Carrying method	Gehä
Breaking load	130

2,5 Installationsrohr 1,2 Gehäuse 130

GTIN: 4021103420607

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.