

## **3-PART RUNG STEPLADDER AND EXTENSION LADDER, 3 X 14 RUNGS**

## Article number: 146214

Attribute

Material

Execution

With wheels


With stabilizers

With leash

3-section rung stepladder and extension ladder, insulating up to 1000 V AC/1500 V DC. Combined three-part rung ladder that can be used both as a stepladder and as an extension ladder (single ladder). When used as a stepladder, the third upper ladder section serves only as a safety bridge. Optimum stability due to floor crossbar, sliding ladder height adjustable from rung to rung by hand, 2 wall rollers at the top end of the ladder, locking and opening mechanism made of aluminum, high-strength tension

belts to prevent unintentional opening of the stepladder, hollow GRP stiles in H-profile (90x32 mm, with 8 rungs 70x32 mm), aluminum rungs in the dimensions: Rung cross-section 27x27 mm, rung spacing 280 mm, tested according to EN 131 (except 3x14 rungs!). Number of rungs: 3x14; stepladder height: 4.00 m; extension ladder height (max.): 10.25; weight: 43 kg. Plastic ladder with tested, extremely age-resistant glass fiber spars, which have an electrically insulating effect, especially for professional

users who work near cables, connections or other current-carrying equipment. Lightweight and easy to handle thanks to the special design of the GRP uprights (hollow or C-profile) and aluminum rungs or steps, rungs and steps permanently flanged twice to the uprights, rung spacing 280 mm: Load capacity 150 kg, non-slip stand due to rubber ladder shoes, including detailed operating, assembly and safety instructions. Ladders comply with European standard EN 131 and electrical tests according to DIN 53



CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.

Value

No

No

No

Glasfaser/Aluminium

Schiebeleiter



With platform	No
Load capacity	150
Number of elements	3
Transport length	4
Number of rungs	14
Rated voltage DC	1500
Rated voltage AC	1000
Complies with EN 50528	No
With mast adapter	No

## GTIN: 4021103462140

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.

## SICHER SEIT 1827.