

## STEPLADDER WITH 2 X 8 STEPS

**Article number: 146508**

Stepladder with steps, insulating up to 1000 V AC/1500 V DC. Fluted aluminum steps on both sides for safe and comfortable standing, especially for lengthy work. Connecting joint made of aluminum, stable folding metal struts on both sides to prevent unintentional opening of the stepladder, load capacity max. 150 kg, rung cross-section "C-profile" 82x30 mm, rung spacing 250 mm, tested according to EN 131. Number/steps: 2x8; height: 2.02 m; weight: 13.6 kg.



Length (mm)	2040 mm
Width (mm)	580 mm
Height (mm)	210 mm
Weight (kg)	10,5 kg

Attribute	Value
Material	Glasfaser/Aluminium
Execution	sonstige
Width	- mm
With wheels	No
With leash	No
With stabilizers	No
With platform	No
Load capacity	150 kg
Number of elements	2
Transport length	2.02 m
Number of rungs	8
Rated voltage DC	1500 V
Rated voltage AC	1000 V
Complies with EN 50528	No
With mast adapter	No
Length	2 m - 2 m
Platform height	- mm
Insulation between 2 rungs	- kV

GTIN: 4021103465080

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de