

STEPLADDER WITH 2 X 10 STEPS

Article number: 146510

Stepladder with steps, insulating up to 1000 V AC/1500 V DC. Fluted aluminum steps on both sides for safe and comfortable standing, especially for lengthy work. Connecting joint made of aluminum, stable folding metal struts on both sides to prevent unintentional opening of the stepladder, load capacity max. 150 kg, rung cross-section "C-profile" 82x30 mm, rung spacing 250 mm, tested according to EN 131. Number/steps: 2x10; height: 2.50 m; weight: 17.2 kg.



| Attribute | Value |
|------------------------|---------------------|
| Material | Glasfaser/Aluminium |
| Execution | sonstige |
| With wheels | No |
| With leash | No |
| With stabilizers | No |
| With platform | No |
| Load capacity | 150 |
| Number of elements | 2 |
| Transport length | 2,5 |
| Number of rungs | 10 |
| Rated voltage DC | 1500 |
| Rated voltage AC | 1000 |
| Complies with EN 50528 | No |
| With mast adapter | No |
| Length | 2,5 - 2,5 |

GTIN: 4021103465103

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de