

CRIMP CABLE LUG IN PIN FORM CU, STANDARD VERSION, CONDUCTOR CROSS-SECTION/PIN 50 MM²/9.5 MM Ø

Article number: 180608

Crimp terminals, pin form Cu, 0.5-6 mm² according to DIN. Technical data; material: Cu-ETP according to DIN EN 13600; surface: electro tin plated ; sleeve seam hard soldered; for strain relieved connection. Cross section: 50; Pin-Ø: 9,5 mm; L1: 45; L2: 20; D1: 9,5; A: 19; B: 9,5; S: 1,8; Weight per 100pcs:~kg: 1,91; Packs per unit: 1

Length (mm)	200 mm
Width (mm)	120 mm
Height (mm)	26 mm
Weight (kg)	0,0191 kg



Attribute	Value
Surface protection	vernickelt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	0 - 0
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Stiftform
Insulation	ohne
Nominal cross-section	50 mm ² - 50 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Maximum current (I _{max})	- A
Flange length	- mm
Pin width (flat pin cable lug)	- mm

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Pin diameter (pin cable lug) | - mm

GTIN: 4021103806081

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de