

TUBULAR CABLE LUG, RING SHAPE, CONDUCTOR CROSS-SECTION/CONNECTION STUD 2.5 MM²/5 MM Ø
Article number: 180672

Tubular cable lug Cu, standard version. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 tubular cable lugs Cu, standard version. Annealed to copper hardness F20. Cross-section: 2.5 mm²; stud-Ø: 5; W: 8; Øi: 2.3; Øe: 3.9; C1: 6.1; C2: 6.6; a: 6.9; L: 20.1; weight per 100pcs ~kg: 0.16; 7 mm: - ; compression 5 mm: 1; PU/pc: 100.



Attribute	Value
Connection thread dimension (metric)	5
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	2,5
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	14
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	verschiedene

GTIN: 4021103806722

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de