

**TUBULAR CABLE LUG, RING SHAPE, CONDUCTOR CROSS-SECTION/CONNECTION STUD 120 MM<sup>2</sup>/8 MM Ø**
**Article number: 180768**

Tubular cable lug Cu, standard version. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 tubular cable lugs Cu, standard version. Annealed to copper hardness F20. Cross-section: 120 mm<sup>2</sup>; stud-Ø: 8; W: 28; Øi: 15; Øe: 19,5; C1: 13; C2: 13,5; a: 26; L: 65,5; weight per 100pcs ~kg: 6,58; 7 mm: 1; crimp 5 mm: 2; PU/pc: 1.



| Attribute                            | Value             |
|--------------------------------------|-------------------|
| Connection thread dimension (metric) | 8                 |
| Connection bracket                   | 180° (horizontal) |
| Number of fixing holes               | 1                 |
| Nominal cross-section                | 120               |
| Surface protection                   | verzinkt          |
| Material                             | Kupfer            |
| Insulated                            | No                |
| AWG size                             | 250 kcmil         |
| Narrow flange design                 | No                |
| Flange shape                         | Ringform          |
| With viewing hole                    | No                |
| Ladder class                         | verschiedene      |

GTIN: 4021103807682

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de