

**TUBULAR CABLE LUG, RING SHAPE, CONDUCTOR CROSS-SECTION/CONNECTION STUD 120 MM<sup>2</sup>/20 MM Ø**
**Article number: 180776**

Tubular cable lug Cu, standard version. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated, other surfaces on request - also suitable for fine stranded conductors according to IEC 228 tubular cable lugs Cu, standard version. Annealed to copper hardness F20. Cross-section: 120 mm<sup>2</sup>; stud-Ø: 20; W: 36; Øi: 15; Øe: 19,5; C1: 22; C2: 22; a: 26; L: 85; weight per 100pcs ~kg: 7,13; 7 mm: 1; compression 5 mm: 2; PU/pc: 1.



Attribute	Value
Connection thread dimension (metric)	20
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	120
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	250 kcmil
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	verschiedene

GTIN: 4021103807767

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de