

**FERRULE INSULATED CROSS-SECTION/TOTAL LENGTH 4.0 MM<sup>2</sup>/20 MM, PART 4, COLOR SERIES 1, 100 PIECES**
**Article number: 180952**

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 1. Technical data, material: Cu-ETP according to DIN EN 13600- surface: electro tin plated - insulation polypropylene - temperature resistance -35°C to +105°C - For easy plugging onto fine stranded copper conductors, prevents damage and splicing. Cross section: 4 mm<sup>2</sup>, length without insulation L2: 12 mm; total length L1: 20 mm; D1: 2.8; S1: 0.2; S2: 0.3; D2: 4.8; insulation color: orange; weight per 100 pcs.: 0.03; pack of 100.



Length (mm)	145 mm
Width (mm)	100 mm
Height (mm)	9 mm
Weight (kg)	0,0003 kg

Attribute	Value
Nominal cross-section	4 mm <sup>2</sup>
Surface protection	verzinkt
Material	Kupfer
Color	orange
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	20 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	12 mm
With identification flag	No

GTIN: 4021103809525

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de