

FLAME-RETARDANT, SELF-EXTINGUISHING CABLE TIES L X W 140 X 3.5 MM, 100 PIECES
Article number: 181728

Fire retardant cable ties made of PA 6.6, flammability class UL 94 V-0. Meets particularly high requirements for flame resistance: the material must not burn for more than 10 seconds and must not ignite flammable materials underneath. Halogen-free, temperature resistance -20 °C to +80 °C. Minimum installation temperature 0 °C. Color milk white.

Length (mm)	275 mm
Width (mm)	95 mm
Height (mm)	22 mm
Weight (kg)	0,00061 kg



Attribute	Value
Surface protection	sonstige
Material	Kunststoff
Material quality	Polyamid (PA)
Color	weiß
Execution	innenverzahnt
Fluorescent	No
Halogen-free	Yes
Mounting type	sonstige
Detectable	No
Transparent	No
Width of the belt	3.5 mm
Detachable closure	No
Labeling area	ohne
Strap fastener	Kunststoffzunge/-nase
Mounting temperature	0 °C - 80 °C
Belt length	140 mm
Operating temperature	-20 °C - 80 °C
Bundle diameter	3 mm - 36 mm
Min. holding force	140 N
UL approval	Yes
UV-stable according to ASTM D6779	Yes
Flammability class of the insulating material according to UL94	V0
Tape thickness	- mm

CIMCO Werkzeuge GmbH & Co. KG
 Hohenagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de



VG approval
MIL approval

No
No

GTIN: 4021103817285

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de