

FERRULE INSULATED CROSS-SECTION/TOTAL LENGTH 0.5 MM²/10 MM, PART 4, COLOR SERIES 2, 100 PIECES
Article number: 182199

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 2. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105°C - For easy plugging onto fine-stranded copper conductors, prevents damage and splicing. Design: cross-section 0.5 mm², length without insulation L2: 10 mm; total length L1: 16 mm; D1: 1; S1: 0.15, S2: 0.25; D2: 2.6; insulation color: orange, weight per 100 pcs.: 0.01; packing unit: 100.



Length (mm)	140 mm
Width (mm)	80 mm
Height (mm)	4 mm
Weight (kg)	0,0001 kg

Attribute	Value
Nominal cross-section	0.5 mm ²
Surface protection	verzinkt
Material	Kupfer
Color	orange
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	16 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	10 mm
With identification flag	No
AWG size	20

GTIN: 4021103821992

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de