

FERRULE INSULATED CROSS-SECTION/TOTAL LENGTH 16.0 MM²/24 MM, PART 4, COLOR SERIES 2, 100 PIECES
Article number: 182218

Insulated ferrules, dimensions according to DIN 46228, part 4, color series 2. Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro tin plated - Insulation polypropylene - Temperature resistance -35°C to +105°C - For easy plugging onto fine-stranded copper conductors, prevents damage and splicing. Design: cross section: 16 mm², length without insulation L2: 12 mm; total length L1: 24 mm; D1: 5.8; S1: 0.2, S2: 0.4; D2: 8.8; insulation color: green, weight per 100 pcs.: 0.08; packing unit: 100.



Length (mm) 145 mm
 Width (mm) 145 mm
 Height (mm) 28 mm
 Weight (kg) 0,0008 kg

Attribute	Value
Nominal cross-section	16 mm ²
Surface protection	verzinkt
Material	Kupfer
Color	grün
Insulated	Yes
Halogen-free	Yes
Strip goods	No
Total length	24 mm
Design	Standard
For short-circuit-proof cables	No
Insulation material	Polypropylen (PP)
Sleeve length	12 mm
With identification flag	No
AWG size	6

GTIN: 4021103822180

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de