

TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS DIN 0295, 16 MM² M 6, 50 PIECES
Article number: 183266

Tubular cable lugs Cu. Version for fine stranded conductors DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 16 mm²; Bolt-Ø: 6 mm; W: 13; Øi: 6,6; Øe: 9,5; C1: 7; C2: 79 a: 14,6; L: 37,6; Weight per 100 pcs.~kg: 1,15; VE/pc. 50



Attribute	Value
Connection thread dimension (metric)	6
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	16
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	6
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	K1.5 = feindrätig

GTIN: 4021103832660

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de