

TUBULAR CABLE LUG CU, VERSION FOR FINE-STRANDED CONDUCTORS DIN 0295, 150 MM² M 20, 1 PIECE
Article number: 183348

Tubular cable lugs Cu. Design for fine stranded conductors according to DIN 0295 and IEC 228. Technical data - Material: Cu-ETP according to DIN EN 13600 - Flared cable entry "Easy Entry"- Surface: electro tin plated, other surfaces on request - Annealed to copper hardness F20. Design: Cross-section: 150 mm²; Bolt-Ø: 20 mm; W: 33; Øi: 18; Øe: 23; C1: 13,5; C2: 21,5; a: 31,5; L: 89; Weight per 100 pcs.~kg: 10,55; PU/pc. 1



Attribute	Value
Connection thread dimension (metric)	20
Connection bracket	180° (horizontal)
Number of fixing holes	1
Nominal cross-section	150
Surface protection	verzinkt
Material	Kupfer
Insulated	No
AWG size	300 kcmil
Narrow flange design	No
Flange shape	Ringform
With viewing hole	No
Ladder class	K1.5 = feindrähtig

GTIN: 4021103833483

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de