

POWER STRIP AUTOMATIC WIRE STRIPPER

Article number: 100770

Automatic wire stripper for a wide range of common cable types in domestic installations, even for problematic insulation such as silicone or the outer sheath of PVC or rubber flex cables (e.g. 3 x 0.75 mm²). Automatic adjustment to the respective conductor cross-section. Working range flexible 0.5 - 16 mm² (20 - 6 AWG), solid 0.5 - 10 mm² (20 - 8 AWG). Precise work thanks to optical length measurement (8 - 24 mm) for consistent stripping lengths when working in series with ferrules or cable lugs. Integration



| | |
|-------------|---------|
| Length (mm) | 163 mm |
| Width (mm) | 35 mm |
| Height (mm) | 235 mm |
| Weight (kg) | 0,24 kg |

| Attribute | Value |
|------------------------------|--|
| Surface protection | sonstige |
| Length | 170 mm |
| Insulated | No |
| Adjustable notch depth | No |
| Round cut | Yes |
| Longitudinal section | No |
| Spiral cut | No |
| Stripping area Cross-section | 0.5 mm ² - 16 mm ² |
| Stripping range Diameter | 1 mm - 12 mm |
| Handle cover | ohne |
| Self-adjusting | Yes |
| Surface treatment | sonstige |
| Adjustable stripping length | No |
| ESD tested | No |
| Handle design | 1-Komponenten |
| Weight | 220 g |
| With wire cutter | Yes |
| Protective insulation 1000 V | No |
| With impact protection | No |
| VDE-tested | No |
| Head height | 40 mm |

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

| | |
|---------------------|--------|
| Head width | 15 mm |
| Length of the jaws | 7 mm |
| Stripping range AWG | 8 - 20 |

GTIN: 4021103007709

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de