

EASYCRIMP MANDREL PRESS

Article number: 106656

The Easycrimp mandrel press can be used to process tubular cable lugs and connectors in standard design as well as crimp cable lugs to DIN 46234 in the range from 10 to 300 mm² without having to change press inserts. The mandrel crimping shape also enables the processing of stranded and fine-stranded conductors in accordance with DIN EN 60228. The crimping head can be rotated through 180 degrees, the maximum processing speed is achieved by a high-performance motor, and an automatic return takes place after crimping is complete. The service cycle is 20,000 operations. The working range is between minus 10 degrees Celsius and plus 60 degrees Celsius. The battery voltage is 18 volts, the battery capacity is 2.0 Ah Li-Ion and the battery charging time is 40 minutes. The scope of delivery includes the crimping tool, a charger, two 2.0 Ah batteries and an LBoxx.



Length (mm)	445 mm
Width (mm)	358 mm
Height (mm)	152 mm
Weight (kg)	7,35 kg

Attribute	Value
Long	445 mm
Execution/actuation	akku-hydraulisch
Suitable for	Cable lugs and connectors
Press mold	Dornpressung
Cross section	10 mm ² - 300 mm ²
With locking device (for mechanical tools)	Yes
Replaceable inserts	No
Number of inserts supplied	1
With automatic return	Yes
Pressure force	62 kN - 62 kN

GTIN: 4021103124659

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de