## **HYDRAULIC CORDLESS CUTTER CIMCUT 55**

## Article number: 106666

DATA SHEET

Pistol-shaped cutting tool: CimCut55, cutting head can be rotated 270°C, 2-stage hydraulics for high-speed feed, manual return after the cut is complete, also suitable for cutting steel bars up to a diameter of 20 mm: Cutting force: 43 kN; For cutting: Fine-stranded Cu cables up to a diameter of 32 mm, Cu/Al underground cables up to a diameter of 51 mm, telecom cables up to a diameter of 55 mm, solid Cu up to a diameter of 18 mm, solid Al up to a diameter of 25 mm; Max. cutting diameter: 55 mm, Cutting diameter: 55 mm. Cutting diameter: 55 mm, cutting time (depending on cross-section): 7-15s; service cycle: 20,000 operations; working range: -10°C to + 60°C; battery voltage: 5.0 Ah-Li-lon; battery charging time: 40 min; guillotine-shaped cutting head, dimensions: 500x335x75, weight: 6,600 g



Length (mm)500 mmWidth (mm)335 mmHeight (mm)75 mmWeight (kg)10,5 kg

Attribute	Value
Cross section	254 mm² - 2042 mm²
Length	500 mm
Execution/actuation	akku-hydraulisch
With automatic return	Yes
Pressing force	43 kN - 43 kN
Cycle time	7 s - 15 s
	•

GTIN: 4021103004258

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

SICHER SEIT 1827.

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.