

BITFLEX BIT, STANDARD, PZ1, LENGTH 25 MM

Article number: 114515

Bitflex bit, the damping zone between the drive and the working tip absorbs excess force peaks, which previously led to high wear and destructive ejection forces. The FLEX zone gives the Bitflex a significantly longer service life compared to conventional standard bits. Bit with 1/4" hexagon drive, STANDARD to DIN 3128, single bit for Phillips screw Pozidriv PZ1, length 25 mm

Length (mm) 25 mm
Width (mm) 7 mm
Height (mm) 7 mm
Weight (kg) 0,005 kg



| Attribute | Value |
|------------------------------|-------------|
| Protective insulation 1000 V | No |
| Total length | 25 mm |
| Two-sided | No |
| Spring ball mounting | No |
| Connection dimension | 1/4 Zoll mm |
| Suitable for use with impact | No |
| With hole | No |
| Size | 1 |
| Type of crosshead | Pozidriv PZ |
| Screw system | Kreuz |
| Bit size | - mm |
| Blade width | - mm |
| Width across flats | - mm |
| Blade thickness | - mm |
| Connection dimension | EV006239 |

GTIN: 4021103145159

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de