

**BITFLEX BIT, STANDARD, PZ2, LENGTH 25 MM**
**Article number: 114516**

Bitflex bit, the damping zone between the drive and the working tip absorbs excess force peaks, which previously led to high wear and destructive ejection forces. The FLEX zone gives the Bitflex a significantly longer service life compared to conventional standard bits. Bit with 1/4" hexagon drive, STANDARD to DIN 3128, single bit for Phillips screw Pozidriv PZ2, length 25 mm



Length (mm)	25 mm
Width (mm)	7 mm
Height (mm)	7 mm
Weight (kg)	0,005 kg

Attribute	Value
Protective insulation 1000 V	No
Total length	25 mm
Two-sided	No
Spring ball mounting	No
Connection dimension	1/4 Zoll mm
Suitable for use with impact	No
With hole	No
Size	2
Type of crosshead	Pozidriv PZ
Screw system	Kreuz
Bit size	- mm
Blade width	- mm
Width across flats	- mm
Blade thickness	- mm
Connection dimension	EV006239

GTIN: 4021103145166

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de