

BITFLEX BIT, STANDARD, T 25, LENGTH 25 MM

0,007 kg

Article number: 114973

Weight (kg)

itflex bit, the damping zone between the drive and the working tip absorbs excess force peaks, which previously led to high wear and destructive ejection forces. The FLEX zone gives the Bitflex a significantly longer service life compared to conventional standard bits. Bit with 1/4" hexagon drive, length 2 mm, single bit for TX screws with hole (Tamper Resistant), without FLEX zone T25, length 25 mm

single bit for TX screws with hole (Tamper Resistant), without

FLEX zone T25, length 25 mm

Length (mm) 25 mm

Width (mm) 7 mm

Height (mm) 7 mm



Attribute	Value
Protective insulation 1000 V	No
Total length	- mm
Two-sided	No
Spring ball mounting	No
Connection dimension	1/4 Zoll mm
Suitable for use with impact	No
With hole	Yes
Screw system	Innensechsrund mit Sicherungsstift (TR)
Bit size	- mm
Blade width	- mm
Width across flats	- mm
Blade thickness	- mm
Connection dimension	EV006239

GTIN: 4021103149737

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de