

VDE SLIM SLOTTED SCREWDRIVER, 4.0 X 0.8 MM

Article number: 117764

1000 V insulated VDE screwdrivers, narrow blade insulation ensures optimum accessibility of deep-lying screws. According to IEC 60900. Classification VDE 0682, part 201. Unit-tested in a water bath with a test voltage of 10,000 volts. GS-approved. Ergonomic triangular handle, resistant to gasoline, thinners and other chemical solvents. VDE Slim slotted screwdriver SLIM 4.0x0.8x100 mm; Total length: 185 mm



Length (mm)	205 mm
Width (mm)	25 mm
Height (mm)	25 mm
Weight (kg)	0,043 kg

Attribute	Value
Execution	gerade
Insulated	Yes
Handle design	2-Komponenten
Weight	43 g
Protective insulation 1000 V	Yes
Total length	205 mm
Size	4
Material of the handle	Kunststoff
Blade diameter	- mm
Blade width	4 mm
Blade length	100 mm
Low-spark version	No
Anti-magnetic	No
Rotatable cap	No
Shank version	rund
Blade material	Chrom-Vanadium-Stahl
With roll-off protection	Yes
Surface protection blade	verchromt
Continuous blade	No
Precision design	No
Clamping device	No
With impact cap	No

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Drive square/hexagon over the entire blade	No
Drive square/hexagon	ohne
Curved blade	No
Blade thickness	- mm
Width across flats (square drive)	- mm
Width across flats (drive hexagon)	- mm

GTIN: 4021103177648

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de