

VDE SLIM SLOTTED SCREWDRIVER, 6.5 X 1.2 MM

Article number: 117770

1,000 V insulated VDE screwdrivers, narrow blade insulation ensures optimum accessibility to deep-set screws. In accordance with IEC 60900, classification VDE 0682, part 201, piece-tested in a water bath with a test voltage of 10,000 volts. GS-tested. Ergonomic triangular handle shape, resistant to petrol, thinners and other chemical solvents. VDE slim slotted screwdriver SLIM 6.5x1.2x150 mm; total length: 265 mm



Length (mm)	265 mm
Width (mm)	34 mm
Height (mm)	34 mm
Weight (kg)	0,1346 kg

Attribute	Value
Execution	gerade
Insulated	Yes
Handle design	2-Komponenten
Weight	134 g
Protective insulation 1000 V	Yes
Total length	265 mm
Material of the handle	Kunststoff
Blade diameter	- mm
Blade width	6.5 mm
Blade length	150 mm
Low-spark version	No
Anti-magnetic	No
Rotatable cap	No
Shank version	rund
Blade material	Chrom-Vanadium-Stahl
With roll-off protection	Yes
Surface protection blade	verchromt
Continuous blade	No
Precision design	No
Clamping device	No
With impact cap	No
Drive square/hexagon over the entire blade	No

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Drive square/hexagon	ohne
Curved blade	No
Blade thickness	- mm
Width across flats (square drive)	- mm
Width across flats (drive hexagon)	- mm

GTIN: 4021103177709

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de