

JOKARI® CABLE KNIFE WITH HOOK BLADE, 8 - 28 MM Ø, STANDARD

Article number: 121010

" Jokari® Cable Knives million times proven cable knives for round and longitudinal cut. Cutting depth individually adjustable via screw, so that damage to the inner conductors is excluded. Handles made of wear-resistant polyamide. Both the tips of the internal cable knives and the cutting edges of the attached bow blades are titanium nitride coated. At approx. 500°C, titanium nitride is vapor-deposited onto the cutting blade in the vacuum chamber using the PVD process. Due to the reduced surface structure and the extremely high hardness, excellent sliding properties and high wear or abrasion resistance are achieved. TiN-coated knives can be used with significantly higher durability and cutting performance. Standard version with enlarged set screw and a hook blade of one from ø 8-28 mm.

Length (mm) 80 mm Width (mm) 31 mm Height (mm) 255 mm Weight (kg) 0,094 kg



CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

SICHER SEIT 1827.



FoldableNoProtective insulation 1000 VNoTotal length165 mmWith protective coverYesWith scraperNoExtendableNoLength of the blade29 mmMaterial of the handleKunststoffBlade shapeHakenformCutter knifeNoCable knifeYesAutomatic retractionNoWith sliding shoeNoBlade materialNoStade materialStatestingStade materialStatestingStatestingStatestingStatestingNoStatestingNoStatestingNoStatestingNoStatestingNoStatestingNoStatestingNoStatestingNoStatestingNoStatestingNoStatestingNoStatestingStatestingStatestingStatestingStatestingStatestingStatestingStatestingStatesting	Attribute	Value
Total length165 mmWith protective coverYesWith scraperNoExtendableNoLength of the blade29 mmMaterial of the handleKunststoffBlade shapeHakenformBlade height- mmCutter knifeNoCable knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	Foldable	No
With protective coverYesWith scraperNoExtendableNoLength of the blade29 mmMaterial of the handleKunststoffBlade shapeHakenformBlade height- mmCutter knifeNoCable knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	Protective insulation 1000 V	No
With scraperNoExtendableNoLength of the blade29 mmMaterial of the handleKunststoffBlade shapeHakenformBlade height- mmCutter knifeNoCutter knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	Total length	165 mm
ExtendableNoLength of the blade29 mmMaterial of the handleKunststoffBlade shapeHakenformBlade height- mmCutter knifeNoCable knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	With protective cover	Yes
Length of the blade29 mmMaterial of the handleKunststoffBlade shapeHakenformBlade height- mmCutter knifeNoCable knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	With scraper	No
Material of the handleKunststoffBlade shapeHakenformBlade height- mmCutter knifeNoCable knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	Extendable	No
Blade shapeHakenformBlade height- mmCutter knifeNoCable knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	Length of the blade	29 mm
Blade height- mmCutter knifeNoCable knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	Material of the handle	Kunststoff
Cutter knifeNoCable knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	Blade shape	Hakenform
Cable knifeYesAutomatic retractionNoWith sliding shoeNoWith locking mechanismNo	Blade height	- mm
Automatic retractionNoWith sliding shoeNoWith locking mechanismNo	Cutter knife	No
With sliding shoe No With locking mechanism No	Cable knife	Yes
With locking mechanism No	Automatic retraction	No
	With sliding shoe	No
Blade material sonstige	With locking mechanism	No
contrage contrage	Blade material	sonstige

GTIN: 4021103210109

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.

SICHER SEIT 1827.