

## BASIC PG 36 SCREW PUNCH

**Article number: 132330**

Screw punch round BASIC suitable for: Sheet steel (ST 37), plastic and aluminum. Operation: Manual and hydraulic, punch waste is punched out 1-piece. Design: With punch, die and ball bearing pulling screw with (encapsulated) : Nominal dimension PG 36 mm, hole dia. 47.0 mm, screw size 19.0x75.0 mm, pilot hole dia. 20.4\*mm, max. material thickness 3.0 mm

|             |          |
|-------------|----------|
| Length (mm) | 73 mm    |
| Width (mm)  | 73 mm    |
| Height (mm) | 140 mm   |
| Weight (kg) | 0,745 kg |



| Attribute                 | Value               |
|---------------------------|---------------------|
| Execution                 | Matrize und Stempel |
| Hole height               | 3 mm                |
| Material to be machined   | Stahl               |
| Hole shape                | rund                |
| Slot punch                | Yes                 |
| Hole diameter             | PG36 mm             |
| Mechanical actuation type | Yes                 |
| Actuation type hydraulic  | Yes                 |
| Hole width                | - mm                |
| Hole diameter             | EV004461            |

GTIN: 4021103323304

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de