

DIAMANT SCREW PUNCH, M 63**Article number: 132514**

Screw Punch Diamond an innovative splitting punch with three cutting tips: Punch waste is split into three parts. Suitable for: Sheet steel (ST 37), plastic and aluminum. Operation: Manual and hydraulic. Design: With punch and die, pull screw with ball bearing. Hole \varnothing 63.5 mm; material thickness 3.0 mm; nominal metric 63 mm; size 2-1/2"; screw size 19.0x75.0 mm; pilot hole \varnothing 20.4*mm.

| | |
|-------------|----------|
| Length (mm) | 105 mm |
| Width (mm) | 95 mm |
| Height (mm) | 135 mm |
| Weight (kg) | 1,245 kg |



| Attribute | Value |
|---------------------------|---------------------|
| Execution | Matrize und Stempel |
| Hole height | 3 mm |
| Material to be machined | Stahl |
| Hole shape | rund |
| Slot punch | Yes |
| Hole diameter | 63.5 mm |
| Mechanical actuation type | Yes |
| Actuation type hydraulic | Yes |
| Hole width | 63.5 mm |
| Hole diameter | EV000154 |

GTIN: 4021103325148

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de