

DIAMANT SCREW PUNCH, PG 9

Article number: 132518

Screw Punch Diamond an innovative splitting punch with three cutting tips: Punch waste is split into three parts. Suitable for: Sheet steel (ST 37), plastic and aluminum. Operation: Manual and hydraulic. Design: With punch and die, pull screw with ball bearing. Hole Ø 15.2 mm; material thickness 2.0 mm; nominal size PG 9; screw size 9.5x50.0 mm; pilot drill Ø 10.0 mm.

Length (mm) 43 mm Width (mm) 43 mm Height (mm) 96 mm Weight (kg) 0,122 kg



Attribute	Value
Execution	Matrize und Stempel
Hole height	2 mm
Material to be machined	Stahl
Hole shape	rund
Slot punch	Yes
Hole diameter	PG9 mm
Mechanical actuation type	Yes
Actuation type hydraulic	Yes
Hole width	- mm
Hole diameter	EV004465

GTIN: 4021103325186

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.