

MIXING PLASTER IN A PAPER BAG, 25 KG

Article number: 140338

For setting gypsum plasterboard, gypsum fiberboard and gypsum plasterboard composite panels on load-bearing and absorbent substrates, smooth concrete surfaces in contact with concrete, pretreat highly absorbent substrates with primer or burn-on barrier, the processing guidelines of the manufacturers of the finishing panels must be observed. Also suitable for setting interior plaster profiles, processing time approx. 50 minutes, material consumption approx. 5 kg/m², storage life approx. 6 months, in paper sack 25 kg PU=1 pallet; 40 sack



Length (mm)	0 mm
Width (mm)	0 mm
Height (mm)	0 mm
Weight (kg)	25 kg

Attribute	Value
Color	grau
Execution	Pulver
Processing time	40 min - 50 min
Drying time	3 h - 4 h
Flexural strength according to EN 998-1	2.5 N/mm ²
Density	- kg/m ³
Compressive strength according to EN 998-1	- N/mm ²
To be tiled according to	- h
For plaster thickness	1 mm - 15 mm
Adhesive strength according to EN 998-1	- N/mm ²
Material requirement per 1 mm layer thickness	- kg/m ²
Max. Grain size according to EN 998-1	- mm
Thermal conductivity according to EN 1745 (lambda-10, dry, P=50 %)	- W/(m.K)
Thermal conductivity according to EN 1745 (lambda-10, dry, P=90 %)	- W/(m.K)

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de



GTIN: 4003230005292

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de