

ADHESIVE PLASTER RED-WHITE, IN PAPER BAG, 25 KG

Article number: 140342

Adhesive plaster gypsum red-white, single-layer interior plaster with adhesive additives and high yield for hand application on all common plaster substrates as well as on rough or smooth concrete surfaces indoors, including domestic kitchens and bathrooms. Pre-treatment with concrete contact is required for smooth substrates. Can be smoothed, felted or applied in free texture, processing time approx. 100 minutes (depending on processing conditions), recommended plaster thickness 8 mm, material consumption approx. 5 m²/25 kg bag at 8 mm plaster thickness, shelf life approx. 6 months, in paper bag 25 kg; PU= 1 pallet; 40 bags.



Length (mm)	0 mm
Width (mm)	0 mm
Height (mm)	0 mm
Weight (kg)	25 kg

Attribute	Value
Color	weiß
Execution	Pulver
Processing temperature	5 °C - 30 °C
Processing time	90 min - 100 min
Drying time	24 h - 48 h
Suitable for bonding interior bricks	No
Lightweight	No
Quick drying	No
Suitable for outdoor use	Yes
Suitable for the top layer	Yes
Suitable for base layer	Yes
Colorable	No
Flexural strength according to EN 998-1	0.2 N/mm ²
Density	875 kg/m ³
Compressive strength according to EN 998-1	3 N/mm ²
Suitable for renovation	Yes
Thermally insulating	No
To be tiled according to	- h

CIMCO Werkzeuge GmbH & Co. KG
 Hohenagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

For plaster thickness	5 mm - 35 mm
Adhesive strength according to EN 998-1	0.2 N/mm ²
Material requirement per 1 mm layer thickness	0.8 kg/m ²
Max. Grain size according to EN 998-1	- mm
Thermal conductivity according to EN 1745 (lambda-10, dry, P=50 %)	- W/(m.K)
Thermal conductivity according to EN 1745 (lambda-10, dry, P=90 %)	- W/(m.K)

GTIN: 4003230005285

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de