

KATIMEX® KATI®-TWIST, LENGTH 25 M, 4.5 MM Ø

Article number: 142545

Katimex[®] Kati[®]Twist, the new wear-resistant polyester belts convince with their high shear stability and low frictional resistance (up to 60 % lower than conventional plastic or steel belts) in empty pipes. Extremely good bending and sliding behavior. Maximum tensile load on initial sleeve (M5): 200 kg. Repairable in case of belt breakage (initial sleeve to be pressed on). Breaking load/tape: 4.0 kN. All Kati[®]Blitz and Kabelmax[®] accessories can be used in a compatible way. Version, with a Ø of 4.5 mm; length 25 m.



Length (mm)450 mmWidth (mm)400 mmHeight (mm)50 mmWeight (kg)0,6 kg

Attribute	Value
Length	25 m
Material	Kunststoff
Material quality	Polyamid (PA)
Color	sonstige
Shape	rund
Threaded connection	Yes
Head shape	sonstige
Twisted	Yes
Diameter of cable guide head	10 mm
Field of application	Installationsrohr
Width/diameter of the pull-in wire	4.5 mm
Material thickness of the pull-in wire	4.5 mm
Carrying method	sonstige
Drum/ring diameter	- mm
Breaking load	407 kg

GTIN: 4021103425459

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.