

**KATIMEX® KATI®-TWIST, LENGTH 25 M, 4.5 MM Ø**
**Article number: 142545**

Katimex® Kati®Twist, the new wear-resistant polyester belts convince with their high shear stability and low frictional resistance (up to 60 % lower than conventional plastic or steel belts) in empty pipes. Extremely good bending and sliding behavior. Maximum tensile load on initial sleeve (M5): 200 kg. Repairable in case of belt breakage (initial sleeve to be pressed on). Breaking load/tape: 4.0 kN. All Kati®Blitz and Kabelmax® accessories can be used in a compatible way. Version, with a Ø of 4.5 mm; length 25 m.



Length (mm)	450 mm
Width (mm)	400 mm
Height (mm)	50 mm
Weight (kg)	0,6 kg

Attribute	Value
Length	25 m
Material	Kunststoff
Material quality	Polyamid (PA)
Color	sonstige
Shape	rund
Threaded connection	Yes
Head shape	sonstige
Twisted	Yes
Diameter of cable guide head	10 mm
Field of application	Installationsrohr
Width/diameter of the pull-in wire	4.5 mm
Material thickness of the pull-in wire	4.5 mm
Carrying method	sonstige
Drum/ring diameter	- mm
Breaking load	407 kg

GTIN: 4021103425459

 CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de