

**KATIMEX® KATI® TWIST 2.0, 20 M, 4.5 MM TAPE Ø**
**Article number: 142570**

Katimex®Kati®Twist 2.0. Easy and fast winding of twisted pull-in tapes thanks to crank function and ergonomic, impact-resistant housing. The extra short initial sleeve allows extremely tight bending radii to be passed, and thanks to triple-twisted plastic pull-in tapes, tensile loads of up to 130 kg (tape/ initial sleeve) are possible without any problems. With its M5 thread, Kati® Twist 2.0 is compatible with the complete range of accessories of the Kati®Blitz or Kabelmax®, pull-in tapes of the Kati® Twist 2.0 can be repaired independently by the user. Ergonomic housing with crank function, 3-strand twisted pull-in tape, very high sliding ability in empty conduit, extremely wear-resistant, tape diameter 4.5 mm. Pulling aid flush and captive integrated in the handle of the housing. Including 1 x pulling aid for Kati®Twist 2.0, 1 x pulling head with eye, brass with thread M5, ø 6 mm and 1 x guiding head with eye, brass with thread M5, ø 7 mm. 20 m



Length (mm)	330 mm
Width (mm)	330 mm
Height (mm)	95 mm
Weight (kg)	1,7 kg

Attribute	Value
Length	20 m
Material	Kunststoff
Material quality	Polyamid (PA)
Color	schwarz
Shape	flach
Threaded connection	Yes
Head shape	sonstige
Twisted	No
Diameter of cable guide head	10 mm
Field of application	Installationsrohr
Width/diameter of the pull-in wire	3 mm
Material thickness of the pull-in wire	4.5 mm
Carrying method	sonstige
Drum/ring diameter	- mm

CIMCO Werkzeuge GmbH & Co. KG  
Hohenhagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de



Breaking load | 407 kg

GTIN: 4021103066171

CIMCO Werkzeuge GmbH & Co. KG  
Hohenhagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de