

X-BLOW MICRO DELUXE

Article number: 146300

The professional blowing device for fiber optic expansion (FttH) on network levels three and four (NE3 & NE4) is ideal for cable diameters of 2 to 4 mm and empty conduits with diameters of 7 or 10 mm. The complete set includes a stand and a compressed air hose. The modular blowing system consists of a manual feed unit, a divisible blowing chamber and a compressed air unit. With high blowing performance, fiber optic cables can be gently inserted into empty conduits or SNR over distances of up to 1,500 meters. Thanks to its low weight and intuitive handling, the installation process is simple and efficient. The compact and site-friendly design makes it easy to work even in confined spaces. The divisible X-Blow® Micro blowing chamber enables the blowing in of pre-assembled fiber optic cables on one side. In addition, the device can be converted without tools and therefore offers flexible use with different cable or empty conduit combinations. The blowing device is designed for cable diameters of 2 to 4 mm and empty conduits of types 2-3 with 7 mm and types 3-4 with 10 mm. It achieves a maximum route length of 1,500 meters and a maximum pressure of 15 bar. The scope of delivery includes two blow-in chambers, a compressed air unit, centering inserts, a fiber optic cutter, 240 ml Glit® Air, an empty conduit cutter and other accessories. A Sortimo case, a tripod and a 5 meter compressed air hose are also included.

640 mm
440 mm
222 mm
8 kg

Attribute Field of application Carrying method

Value sonstige sonstige





CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

SICHER SEIT 1827.

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.