

X-BLOW MICRO PROFESSIONAL

Article number: 146301

Professional blowing device in fiber optic expansion (FttH) on network levels three and four (NE3 & NE4) for cable Ø 2 to 4 mm and empty conduit Ø 7 or 10 mm. Complete set with stand and compressed air hose. Modular blowing system with manual feed unit, divisible blowing chamber and compressed air unit. With high blowing performance, fiber optic cables are gently inserted into empty conduits or SNR over a distance of up to 1,500 meters. Low weight and intuitive handling for easy installation. Compact and site-friendly design makes it easy to work even in confined spaces. Divisible X-Blow® Micro blowing chamber for blowing in single-sided pre-assembled fiber optic cables. Simple, tool-free conversion for flexible use with different cable or conduit combinations. Cable Ø 2 to 4 mm, empty conduit Ø type 2-3: 7 mm, empty conduit Ø type 3-4: 10 mm, max. route length: 1500 m, max. pressure: 15 bar. Scope of delivery: 2 blow-in chambers, compressed air unit, centering inserts, fiber optic shears, 240 ml Glit® Air, conduit cutter and other accessories incl. Sortimo case.



Length (mm)	640 mm
Width (mm)	440 mm
Height (mm)	222 mm
Weight (kg)	6 kg

Attribute	Value
Field of application	sonstige
Carrying method	sonstige

GTIN: 4021103109090

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de