

## HEIGHT-ADJUSTABLE ALUMINUM TELESCOPIC LADDER INCLUDING TRAVERSE WITH 2 X 10 STEPS

### Article number: 146710

Height-adjustable aluminum telescopic ladder, including traverse. Flexible 3-in-1 aluminum rung ladder, can be used as a single ladder, push-up ladder or stepladder. Both sides of the ladder can be extended separately from rung to rung, making it suitable for use on sloping surfaces and stairs. Lightweight, handy, easy to use and professionally equipped and finished, max. load capacity 140 kg, optimum stability thanks to rubber feet, strong automatic aluminum joints. Absolutely safe and convenient locking of the ladder thanks to 4 locking elements with spring bolts, locking hooks and covers made of unbreakable plastic. With practical plastic tool holder 310x260 mm. Continuously ribbed, flanged aluminum rungs, rung cross-section 27x27 mm, rung spacing 280 mm, tested in accordance with EN 131. Number of steps: 2x8; height min. 1.25 m; height max. 5.22 m; weight: 13.2 kg.



Length (mm)	1530 mm
Width (mm)	630 mm
Height (mm)	190 mm
Weight (kg)	13,2 kg

Attribute	Value
Material	Aluminium
Execution	Mehrzweckleiter
Width	- mm
Weight	13 kg
With wheels	No
With platform	No
Load capacity	140 kg
Number of elements	2
Transport length	2.51 m
Number of rungs	10
Length	5.2 m - 2.51 m
Platform height	- mm

CIMCO Werkzeuge GmbH & Co. KG  
Hohenagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de



GTIN: 4021103467107

CIMCO Werkzeuge GmbH & Co. KG  
Hohenhagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de