


CORROSION PROTECTION TAPE, BLACK, 50 MM X 33 M

Article number: 160282

Anti-corrosion tapes, extra strong PVC film, coated on one side with non-corrosive, aggressive adhesive, highly durable PVC adhesive tapes with high abrasion resistance, UV resistance and water resistance (also salt water), resistant to alkalis and many acids, microorganisms, bitumen compatible, as an outer wrap for additional protection against wear due to abrasion, weathering and corrosion, thus extending service life and reducing frequent maintenance work, as stone chip, tread and scratch protection for exposed and buried cables, pipes and joints of cables and pipelines, corrosion protection of exposed cables and pipelines (e.g. on ships, in ships' cabins, in the sea, in the sea, etc.). e.g. on ships, in wet plants, in the chemical industry), excellent mechanical and corrosion protection for installation pipes and poles inserted into the ground, base protection for electrical appliances (washing machines, dryers, freezers). Tape thickness 0.44 mm, for particularly heavy duty. Execution in the color black; WxL: 50 mmx33 m.

Length (mm)	155 mm
Width (mm)	25 mm
Height (mm)	25 mm
Weight (kg)	1,011 kg

Attribute	Value
Length	33 m
Material	Polyvinylchlorid (PVC)
Color	schwarz
Fluorescent	No
Photoluminescent	No
UV-resistant	Yes
Width	50 mm
Strength	0.44 mm
Waterproof	No
Magnetic	No
Transparent	No
Double-sided	No
Self-welding/amalgamating	No



CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.



Temperature resistance	0 °C - 85 °C
Insulating	0 °C - 85 °C Yes
Suitable for high voltage	No
Self-extinguishing	No
Vulcanizing	No
Can be torn off by hand	No

GTIN: 5017374611478

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.