UNIVERSAL FABRIC TAPE, YELLOW 15 MM X 50 M

Article number: 162004

DATA SHEET

Universal quality fabric tape, an extruded fabric tape, coated on one side with waterproof polyethylene coating, on the other side with an aggressive, non-corrosive pressure sensitive adhesive. Matt, water- and weather-resistant finish, very good markability with pencil, ballpoint pen, permanent marker, felt-tip pen and etching pen, printable, largely resistant to many chemicals, insensitive to plasticizers and oil vapors, very good electrical properties, easily and particularly cleanly torn off crosswise by hand. Universal fabric adhesive tape for trade and industry: colored identification and marking of cables, electrical components, pipes and ducts, labeling of control cabinets, distributions, patch panels, for bundling, fixing, securing and reinforcing cables and pipes, for masking during painting and varnishing work. Execution in the color yellow. WxL: 15 mmx50 m.

Length (mm)	170 mm
Width (mm)	15 mm
Height (mm)	15 mm
Weight (kg)	0,275 kg

Control of the second	

Attribute	Value
Length	50 m
Material	Gewebe
Color	gelb
Fluorescent	No
Photoluminescent	No
UV-resistant	No
Width	15 mm
Strength	0.31 mm
Waterproof	No
Magnetic	No
Transparent	No
Double-sided	No
Self-welding/amalgamating	No
Temperature resistance	0 °C - 95 °C
Insulating	No

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.



Suitable for high voltage	No
Self-extinguishing	No
Vulcanizing	No
Can be torn off by hand	No No No No
	1

GTIN: 5017374617135

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

SICHER SEIT 1827.

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.