UNIVERSAL FABRIC TAPE, GREEN 50 MM X 50 M

Article number: 162056

DATA SHEET

Universal quality fabric tape, an extruded fabric tape, coated on one side with waterproof polyethylene coating, on the other side with an aggressive, non-corrosive pressure sensitive adhesive. Matt, water- and weather-resistant finish, very good markability with pencil, ballpoint pen, permanent marker, felt-tip pen and etching pen, printable, largely resistant to many chemicals, insensitive to plasticizers and oil vapors, very good electrical properties, easily and particularly cleanly torn off crosswise by hand. Universal fabric adhesive tape for trade and industry: colored identification and marking of cables, electrical components, pipes and ducts, labeling of control cabinets, distributions, patch panels, for bundling, fixing, securing and reinforcing cables and pipes, for masking during painting and varnishing work. Execution in the color green; WxL: 50 mmx50 m.

Length (mm)	165 mm
Width (mm)	50 mm
Height (mm)	50 mm
Weight (kg)	0,916 kg

10 10 10 10 10 10 10 10

Length50 mMaterialGewebeColorgrünFluorescentNoPhotoluminescentNoUV-resistantNoWidth50 mmStrength0.31 mmWaterproofNoMagneticNoDouble-sidedNoSelf-welding/amalgamatingNo	Attribute	Value
ColorgrünFluorescentNoPhotoluminescentNoUV-resistantNoWidth50 mmStrength0.31 mmWaterproofNoMagneticNoTransparentNoDouble-sidedNo	Length	50 m
FluorescentNoPhotoluminescentNoUV-resistantNoWidth50 mmStrength0.31 mmWaterproofNoMagneticNoTransparentNoDouble-sidedNo	Material	Gewebe
PhotoluminescentNoUV-resistantNoWidth50 mmStrength0.31 mmWaterproofNoMagneticNoTransparentNoDouble-sidedNo	Color	grün
UV-resistantNoWidth50 mmStrength0.31 mmWaterproofNoMagneticNoTransparentNoDouble-sidedNo	Fluorescent	No
Width50 mmStrength0.31 mmWaterproofNoMagneticNoTransparentNoDouble-sidedNo	Photoluminescent	No
Strength0.31 mmWaterproofNoMagneticNoTransparentNoDouble-sidedNo	UV-resistant	No
WaterproofNoMagneticNoTransparentNoDouble-sidedNo	Width	50 mm
MagneticNoTransparentNoDouble-sidedNo	Strength	0.31 mm
Transparent No Double-sided No	Waterproof	No
Double-sided No	Magnetic	No
	Transparent	No
Self-welding/amalgamating No	Double-sided	No
	Self-welding/amalgamating	No
Temperature resistance 0 °C - 95 °C	Temperature resistance	0 °C - 95 °C
Insulating No	Insulating	No

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.

SICHER SEIT 1827.



Suitable for high voltage	No
Self-extinguishing	No
Vulcanizing	No No No No
Can be torn off by hand	No

GTIN: 5017374616541

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.