

## INSULATING TAPE SELF-WELDING FOR EXTREME TEMPERATURES COLOR BLACK, 19 MM X 10 M

## Article number: 162830

Self-welding insulating tape for extreme temperatures. A cold-welding insulating tape made of polyethylene, provided with an easily peelable plastic release liner. Welds processing under slight tensile stress to a solid air- and water-tight mass, extremely stretchable (elongation at break 600 %) and conformable, permanently elastic, compatible with all materials for insulation and sheathing, exceptionally wide application temperature range, very good electrical properties (esp. dielectric strength), resistant to ozone, weathering and aqing, excellent resistance to alkalis, hydraulic fluids and other chemical substances. Used in the same way as high-voltage insulating tape (CIMCO article no. 16 2840-16 2841, but with the addition of excellent resistance to very high and very low temperatures (-35°C to +95°C, up to 130°C for short periods) and to many chemicals, for demanding insulation work up to 34 kV/mm and for maintaining chemical resistance at elevated temperatures. Execution in the color black; WxL: 19 mmx10 m.

|--|

Length (mm)	95 mm
Width (mm)	19 mm
Height (mm)	19 mm
Weight (kg)	0,143 kg

Attribute	Value
Length	10 m
Material	sonstige
Color	schwarz
Fluorescent	No
Photoluminescent	No
UV-resistant	Yes
Width	19 mm
Strength	0.44 mm
Waterproof	No
Magnetic	No
Transparent	No
Double-sided	Yes
Self-welding/amalgamating	Yes

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.



Temperature resistance	-35 °C - 130 °C
Insulating	Yes
Suitable for high voltage	Yes
Self-extinguishing	No
Vulcanizing	Yes
Can be torn off by hand	No

GTIN: 5017374615001

CIMCO Werkzeuge GmbH & Co. KG Hohenhagener Straße 1 – 5 42855 Remscheid Telefon +49 2191 3718-01 info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.