

PHOTOVOLTAIC CONNECTOR MALE, 1 PIECE

Article number: 180001

Photovoltaic connector system. The use of this new photovoltaic connector saves work and time on the construction site. The Cimco connector system is compatible with the MC4 market standard and is suitable for all common solar cables from 2.5 mm² to 6 mm². Consisting of connector system plug and socket incl. plastic housing, packed per 100 plug crimp contacts and plastic housing in a polybag and per 100 socket crimp contacts and plastic housing in a polybag. Technical data: 2.5 to 6 mm², voltage range: 1,000 V, current carrying capacity: 30 A (4 mm², 6 mm²), diameter of plug contact: 4 mm, protection class: IP 68, temperature range: -40°C / +85°C, insulation material: PC/PA, contact material: copper, silver-plated, safety class: II, certification: TÜV, crimping range: 2.5 - 6 mm².
Version: male



| | |
|-------------|----------|
| Length (mm) | 340 mm |
| Width (mm) | 210 mm |
| Height (mm) | 40 mm |
| Weight (kg) | 0,011 kg |

| Attribute | Value |
|------------------------------|--------------|
| Suitable for | Photovoltaik |
| Type of accessory/spare part | Stecker |
| Spare part | Yes |
| Accessories | Yes |

GTIN: 4021103800010

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de