

INSULATED CRIMP TERMINALS, FORK-SHAPED CU, CROSS-SECTION 0.1 - 0.4 MM², STUD 3 MM Ø
Article number: 180118

Crimp terminals, fork form Cu, insulated, DIN 46237 from 0,5 - 6 mm². Technical data - Material: Cu-ETP according to DIN EN 13600 - Surface: electro-tinned - For strain-relieved connections - Insulation PA (polyamide, nylon), halogen-free - Temperature resistance -60°C to +105°C, 600 V max.,- Easy Entry enables simple and fast insertion of the conductor. Design: cross-section: 0.1 - 0.4 mm², bolt-Ø: 3 mm, yellow, D1: 1; D2: 3.2; D3: 3.3; A1: 10.5; B 5; L: 16; weight per 100 pcs. ~: 0.04 kg; according to DIN: -; UL listed: -; PU/pc.: 100



Length (mm)	180 mm
Width (mm)	100 mm
Height (mm)	4 mm
Weight (kg)	0,00037 kg

Attribute	Value
Connection thread dimension (metric)	3
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	21 - 27
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Gabelform
Insulation	Polyamid (PA)
Nominal cross-section	0.1 mm ² - 0.4 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Color of the insulation	gelb
Maximum current (I _{max})	- A
Flange length	- mm
Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103801185

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de