

**INSULATED CRIMP TERMINALS, FORK-SHAPED CU, CROSS-SECTION 1.5 - 2.5 MM<sup>2</sup>, PIN 3 MM Ø**
**Article number: 180140**

Crimp-on cable lugs, fork-shaped Cu, insulated. Technical data  
 - Material: Cu-ETP to DIN EN 13600 - Surface: galvanically tin-plated - For strain-relieved connections - Insulation PA (polyamide, nylon), halogen-free - Temperature resistance -60°C to +105°C, 600 V max.,- Easy Entry enables quick and easy insertion of the conductor. Design: Cross-section: 1.5 - 2.5 mm<sup>2</sup>, bolt Ø: 3 mm, nominal size according to DIN: 3-2.5, blue, D1: 2.3; D2: 4.5; D3: 3.2; A1: 11.5; B 5.9; L: 17; Weight per 100 units: 0.08 kg; according to DIN: x; UL listed: x; PU/unit: 100



Length (mm)	150 mm
Width (mm)	85 mm
Height (mm)	12 mm
Weight (kg)	0,00075 kg

Attribute	Value
Connection thread dimension (metric)	3
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	13 - 15
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Gabelform
Insulation	Polyamid (PA)
Nominal cross-section	1.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup>
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de

Color of the insulation	blau
Maximum current (I <sub>max</sub> )	- A
Flange length	- mm
Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103801406

CIMCO Werkzeuge GmbH & Co. KG  
Hohenagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de