

INSULATED CRIMP TERMINALS, FORK-SHAPED CU, CROSS-SECTION 4 - 6 MM², PIN 10 MM Ø
Article number: 180168

Crimp-on cable lugs, fork-shaped Cu, insulated. Technical data
 - Material: Cu-ETP to DIN EN 13600 - Surface: galvanical-ly tin-plated - For strain-relieved connections - Insulation PA (polyamide, nylon), halogen-free - Temperature resistance -60°C to +105°C, 600 V max.,- Easy Entry enables quick and easy insertion of the conductor. Design: Cross-section: 4-6 mm², bolt Ø: 10 mm, nominal size according to DIN: 10-6, yellow, D1: 3.6; D2: 6.8; D3: 10.5; A1: 13; B 19.2; L: 27; Weight per 100 pcs ~: 0.3 kg; according to DIN: x; UL listed: x; PU/unit: 100



Length (mm)	170 mm
Width (mm)	100 mm
Height (mm)	33 mm
Weight (kg)	0,00304 kg

Attribute	Value
Connection thread dimension (metric)	3
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	9 - 11
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Gabelform
Insulation	Polyamid (PA)
Nominal cross-section	4 mm ² - 6 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Color of the insulation	gelb
Maximum current (I _{max})	- A
Flange length	- mm
Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103801680

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de