

**PIN-TYPE CRIMP TERMINALS CU, CROSS-SECTION 0.1 - 0.4 MM<sup>2</sup>, PIN LENGTH 9 MM**
**Article number: 180220**

Crimp terminals, pin form CU, insulated, DIN 46231, from 0.5-6 mm<sup>2</sup>. Technical data: Material: Cu-ETP according to DIN EN 13600, Surface: electro-tinned, other surfaces on request, for strain-relieved connections, insulation PA (polyamide, nylon), halogen-free, temperature resistance -60 °C to +105 °C, 600 V max., Easy Entry enables simple and fast insertion of the conductor. Cross section: 0.1-0.4 mm<sup>2</sup>; pin length: 9 mm, insulation color acc. to DIN: yellow, L1: 20; L2: 9; D1: 1; B: 1; weight per 100pcs. ~kg: 0.05; acc. to DIN: - ; UL listed: - ; PU/pc. 100.



Length (mm)	180 mm
Width (mm)	100 mm
Height (mm)	4 mm
Weight (kg)	0,0005 kg

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	21 - 27
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Stiftform
Insulation	Polyamid (PA)
Nominal cross-section	0.1 mm <sup>2</sup> - 0.4 mm <sup>2</sup>
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Color of the insulation	gelb

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de

Maximum current (I <sub>max</sub> )	- A
Flange length	- mm
Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103802205

CIMCO Werkzeuge GmbH & Co. KG  
Hohenhagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de