

PIN-TYPE CRIMP TERMINALS CU, CROSS-SECTION 4 - 6 MM², PIN LENGTH 11 MM
Article number: 180226

Crimp terminals, pin form CU, insulated, DIN 46231, from 0.5-6 mm². Technical data: Material: Cu-ETP according to DIN EN 13600, Surface: electro-tinned, other surfaces on request, for strain-relieved connections, Insulation PA (polyamide, nylon), halogen-free, Temperature resistance -60 °C to +105 °C, 600 V max, Easy Entry allows easy and fast insertion of the conductor. Cross section: 4-6 mm²; pin length: 11 mm, nominal size: 6; insulation color according to DIN: yellow, L1: 27; L2: 11; D1: 3,6; B: 2,7; weight per 100pcs. ~kg: 0,19; according to DIN: x ; UL listed: -x; PU/pc. 100.



Length (mm)	150 mm
Width (mm)	85 mm
Height (mm)	24 mm
Weight (kg)	0,00185 kg

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	9 - 11
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Stiftform
Insulation	Polyamid (PA)
Nominal cross-section	4 mm ² - 6 mm ²
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de

Color of the insulation	gelb
Maximum current (I _{max})	- A
Flange length	- mm
Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103802267

CIMCO Werkzeuge GmbH & Co. KG
Hohenagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de