

**PIN-TYPE CRIMP TERMINALS CU, CROSS-SECTION 10 MM<sup>2</sup>, PIN LENGTH 11 MM**
**Article number: 180227**

Crimp terminals, pin form CU, insulated, DIN 46231, from 0.5-6 mm<sup>2</sup>. Technical data: Material: Cu-ETP according to DIN EN 13600, Surface: electro-tinned, other surfaces on request, for strain-relieved connections, Insulation PA (polyamide, nylon), halogen-free, Temperature resistance -60 °C to +105 °C, 600 V max, Easy Entry allows easy and fast insertion of the conductor. Cross section: 10 mm<sup>2</sup>; Pin length: 11 mm, Insulation color acc. to DIN: red, L1: 33; L2: 11; D1: 4,3; B: 4,3; Weight per 100pcs. ~kg: 0,31; acc. to DIN: - ; UL listed: -x; PU/pc. 100.



Length (mm)	150 mm
Width (mm)	85 mm
Height (mm)	24 mm
Weight (kg)	0,00312 kg

Attribute	Value
Surface protection	verzinkt
Material	Kupfer
Halogen-free	Yes
Strip goods	No
Total length	- mm
AWG range	7 - 7
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine-stranded conductors	Yes
Corresponds to DIN	Yes
Sleeve shape	kurz
Flange shape	Stiftform
Insulation	Polyamid (PA)
Nominal cross-section	10 mm <sup>2</sup> - 10 mm <sup>2</sup>
For tensile strength connections	No
Suitable for round conductors	Yes
Suitable for high temperatures (up to 650 °C)	No
Suitable for flat conductors	No
Suitable for enameled wire	No
Color of the insulation	rot

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de

Maximum current (I <sub>max</sub> )	- A
Flange length	- mm
Pin width (flat pin cable lug)	- mm
Pin diameter (pin cable lug)	- mm

GTIN: 4021103802274

CIMCO Werkzeuge GmbH & Co. KG  
Hohenhagener Straße 1 – 5  
42855 Remscheid  
Telefon +49 2191 3718-01  
info@cimco.de • cimco.de