

**FLAT RECEPTACLE, FULLY INSULATED, 1.5 - 2.5 MM<sup>2</sup>, PLUG DIMENSION 2.8 X 0.8 MM**
**Article number: 180247**

Receptacles, fully insulated - Technical data - Material: CuZn (brass) - Surface: electro-tinned - Insulation: fully insulated PA (polyamide, nylon), halogen-free - Temperature resistance -60°C to +105°C - 600 V max.- Easy Entry enables simple and fast insertion of the conductor. Cross section: 1.5 - 2.5 mm<sup>2</sup> ; Plug dimension: 2.8x0.8 mm; Insulation color: blue; L1: 20; L2: 8; D1: 2.3; Weight per 100pcs ~kg: 0.09; UL listed: x; Packs of 100.



|             |            |
|-------------|------------|
| Length (mm) | 180 mm     |
| Width (mm)  | 100 mm     |
| Height (mm) | 11 mm      |
| Weight (kg) | 0,00094 kg |

| Attribute                           | Value                                     |
|-------------------------------------|---|
| Surface protection                  | verzinkt                                  |
| Material                            | Messing                                   |
| Execution                           | Hülse                                     |
| Halogen-free                        | Yes                                       |
| Insulation material                 | Polyamid (PA)                             |
| AWG range                           | 14 - 16                                   |
| Insulation                          | vollisoliert                              |
| Nominal cross-section               | 1.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> |
| Color of the insulation             | blau                                      |
| Plug dimensions                     | flach 2,8x0,8 mm                          |
| With latching nose                  | No  |
| With tap                            | No  |
| Maximum current (I <sub>max</sub> ) | - A                                       |

GTIN: 4021103802472

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de