

FLAT PLUG, INSULATED CROSS-SECTION/PLUG DIMENSION 0.5 - 1 MM²/4.8 X 0.8 MM
Article number: 180288

Flat plug, insulated - Technical data - Material: CuZn (brass)
 - Surface: electro-tinned - Insulation PA (polyamide, nylon),
 halogen-free Temperature resistance -60°C to +105°C - Easy
 Entry enables simple and fast insertion of the conductor.
 Cross-section: 0.5-1 mm²; Plug dimension: 4.8x0.8 mm, Insula-
 tion color: red; L1: 14.6; L2: 5.5; Weight per 100 pcs. ~ kg: 0.09;
 Packs of 100



Length (mm)	150 mm
Width (mm)	90 mm
Height (mm)	7 mm
Weight (kg)	0,00079 kg

Attribute	Value
Surface protection	verzinkt
Material	Messing
Execution	Stecker
Halogen-free	Yes
Insulation material	Polyamid (PA)
AWG range	18 - 20
Insulation	vollisoliert
Nominal cross-section	0.5 mm ² - 1 mm ²
Color of the insulation	rot
Plug dimensions	flach 4,8x0,8 mm
With latching nose	No
With tap	No
Maximum current (I _{max})	- A

GTIN: 4021103802885

CIMCO Werkzeuge GmbH & Co. KG
 Hohenhagener Straße 1 – 5
 42855 Remscheid
 Telefon +49 2191 3718-01
 info@cimco.de • cimco.de