

**FLAT PLUG, INSULATED CROSS-SECTION/PLUG DIMENSION 4 - 6 MM<sup>2</sup>/6.3 X 0.8 MM**
**Article number: 180294**

Flat plug, insulated - Technical data - Material: CuZn (brass)  
 - Surface: electro-tinned - Insulation PA (polyamide, nylon),  
 halogen-free Temperature resistance -60°C to +105°C - Easy  
 Entry enables simple and fast insertion of the conductor.  
 Cross section: 4-6 mm<sup>2</sup>; Plug dimension: 6,3x0,8 mm, Insulation  
 color: yellow; L1: 22; L2: 7,5; Weight per 100 pcs. ~ kg: 0,16;  
 Packing unit 100



Length (mm)	180 mm
Width (mm)	90 mm
Height (mm)	13 mm
Weight (kg)	0,00162 kg

Attribute	Value
Surface protection	verzinkt
Material	Messing
Execution	Stecker
Halogen-free	Yes
Insulation material	Polyamid (PA)
AWG range	10 - 12
Insulation	teilsoliert
Nominal cross-section	4 mm <sup>2</sup> - 6 mm <sup>2</sup>
Color of the insulation	gelb
Plug dimensions	flach 6,3x0,8 mm
With latching nose	No
With tap	No
Maximum current (I <sub>max</sub> )	- A

GTIN: 4021103802946

CIMCO Werkzeuge GmbH & Co. KG  
 Hohenhagener Straße 1 – 5  
 42855 Remscheid  
 Telefon +49 2191 3718-01  
 info@cimco.de • cimco.de